

## 1575/1576

## Electromagnetic Gate Locks

SDC's magnetic gate locks provide 1200lbs of holding force and enable the access and egress control of pedestrian and vehicle gates. Access controls such as card readers, digital keypads and remote control stations provide gate and lock control.

Compatible with manual and automatic, swinging and sliding, tubular and iron gates. The floating armature design compensates for gate misalignment with the electromagnet.

SDC magnetic gate locks are totally sealed in an epoxy filled stainless steel case. A threaded conduit fitting ensures weather resistant protection of the wiring.

- · Epoxy sealed electronics
- · Threaded conduit fitting
- · Stainless steel housing
- · Wire leads, 3 feet
- · Field selectable dual voltage
- · Voltage and current spike protection
- Low power consumption
- Door position status (DPS)
- · Bond alert status (BAS)

MODEL		LIST \$
1575U	Gate Single Magnetic Lock, 1200lbs, Weatherized, 630, DPS, BAS	539.00
1576U	Gate Single Magnetic Lock, Face-Drilled, 1200lbs, Weatherized, 630, DPS, BAS	539.00

## **RELATED PRODUCTS**

When you order any SDC products in this section, there are a number of related or complementary products that have proven to work well with your selection.

1575-BK	1575 Angle Bracket, 2" x 2%" x 81½ 6"	127.00
1576-AB	1576 Armature Mounting Bracket, 2¾" x 3¼" x 10%"	101.00
1576-BK	1576 Angle Bracket, 1 <sup>13</sup> /16" x 2³/4" x 8 <sup>11</sup> /16"	101.00
1576-MP	1576 Lock Body Mounting Plate, 1/4" x 21/2" x 811/16"	71.00
1576-ZBV*	1576 Z Bracket, 51/16" x 3%" x 101/8"	200.00

<sup>\*</sup>Includes 1576-MP mounting plate.